## Environmental Class® Particleboard Core Doors Neutral Pressure (12) - NON-RATED(EPCUF-1) and 20-MINUTE(EPCUF-20)

**Product Features** and Specifications

**Thickness** 

**Faces** 

Crossbands

Interior Only (1)

1-3/4" , 1-3/8" , 2", 2-1/4"

**Maximum Size** EPCUF-1: Single: 4/0 x 10/0

Pair: 8/0 x 10/0 EPCUF-20: ITS-WH & UL

1-3/4": **Single:** 4/0 x 10/0 **Pair:** 8/0 x 10/0 Double Egress Pair: 8/0 x 8/0

1-3/8": Single only: 3/0 x 7/0

Minimum Size 0/8 x 1/10 (32)

· Wood Veneer · Decorative Laminate

• MDO • Primed MDO • Styled® Door Face Urea Formaldehyde Free Engineered Fiber

Stiles LSL with veneer band or decorative laminate to match face. (2,3)

**Top and Bottom Rails** 7/8" Mill Option (4,5,24,25)

**Face Assembly Adhesive** Core Assembly Adhesive

Core

Type I (waterproof) Type II (water-resistant)

Particleboard core (which complies with ANSI A208.1)

Urea Formaldehyde Free Construction

Lite Openings (6) **METAL VISION FRAMES or WOOD MOULDING:** 

> EPCUF-1: Total area of openings not to exceed 1,296 sq. in. of visible

glass or one continuous dimension of 38" W or 54" H •Divided Lites •Logo Glass •Custom Lites Divided lites and logo glass are for EPCUF-1 only.

See Glazing Table

Other Detail Work (7,21) Grilles Fitting Machining Applied Mouldings Reveals Radius Lites

· Clear or Stain w/ Enviroclad UV® finish Factory Finish (8)

 Opaque with flat gloss topcoat Full; life of original installation (1) Warrantv

Security Rating Class 40 (9), highest Security Rating possible

STC 31 (Inoperable) Acoustic Rating (11)

\*Refer to separate page for explanation of footnotes.










©FSC Trademark 1996 Forest Stewardship Council A.C.



STII F

Note: Marshfield DoorSystems, Inc. doors are manufactured per the standards listed on this page. Specifications are subject to change without notice.